

Technical data sheet

Adapter

Part no.: 50110650

KD 01-5-BA-PWR

Contents

- Technical data
- Electrical connection
- Accessories



For illustration purposes only

Technical data

Electrical data

Performance data

Rated operating current	4,000 mA
Rating voltage (DIN EN 60664-1)	125 V
Rated impulse voltage (DIN EN 60664-1)	1,500 V

Connection

Number of connections	2 Piece(s)
-----------------------	------------

Connection 1

Type of connection	Connector
Thread size	M12
Type	Female
No. of pins	5 -pin
Encoding	A-coded
Version	Axial

Connection 2

Type of connection	Jack socket
--------------------	-------------

Cable properties

AWG	18
-----	----

Mechanical data

Width across flats	18 mm
Mating cycles, max.	> 50
Cable hole	4 ... 6 mm

Environmental data

Ambient temperature, operation	-40 ... 85 °C
--------------------------------	---------------

Certifications

Degree of protection	IP 67
----------------------	-------

Classification

Customs tariff number	85366990
-----------------------	----------

ECLASS 5.1.4	27279201
--------------	----------

ECLASS 8.0	27440104
------------	----------

ECLASS 9.0	27069190
------------	----------

ECLASS 10.0	27440106
-------------	----------

ECLASS 11.0	27440106
-------------	----------

ECLASS 12.0	27440106
-------------	----------

ECLASS 13.0	27440106
-------------	----------

ECLASS 14.0	27440106
-------------	----------

ECLASS 15.0	27440106
-------------	----------

ETIM 5.0	EC002498
----------	----------

ETIM 6.0	EC002498
----------	----------

ETIM 7.0	EC002925
----------	----------

ETIM 8.0	EC002925
----------	----------

ETIM 9.0	EC002925
----------	----------

ETIM 10.0	EC002925
-----------	----------

Electrical connection

Connection 1

Type of connection	Connector
Thread size	M12
Type	Female
No. of pins	5 -pin
Encoding	A-coded
Version	Axial

Connection 2

Type of connection	Jack socket
--------------------	-------------

Accessories

Power supply units

	Part no.	Designation	Article	Description
	50110748 *	NT 24-24W	Power supply unit	Type of power supply unit: Plug-in power supply unit Output: 24 V DC, 1 A Input: 110..240 V AC, 50..60 Hz

* Necessary accessories, please order separately

Accessories

Note	
	A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.