Technical data sheet
Connection unit
Part no.: 50136698
NTS 2

Contents

For Illustration purposes only

Leuze

Connection

Connection 1

Type of connection	Terminal

Mechanical data

Dimension (W x H x L)	102 mm x 42 mm x 228 mm
Housing material	Plastic
Plastic housing	ABS
Net weight	365 g
Housing color	Black

Operation and display

Type of display	Acoustic
	LED indicator

Environmental data

Ambient temperature, operation	-20 ... 60 °C
Ambient temperature, storage	-30 ... 70 °C

Certifications

Degree of protection	IP 40
Protection class	II

Classification

Customs tariff number	85389091
ECLASS 5.1.4	27270990
ECLASS 8.0	27270990
ECLASS 9.0	27379201
ECLASS 10.0	27270992
ECLASS 11.0	27270992
ECLASS 12.0	27270992
ECLASS 13.0	27270992
ECLASS 14.0	27270992
ECLASS 15.0	27270992
ECLASS 16.0	27270992
ETIM 5.0	EC002498
ETIM 6.0	EC003015
ETIM 7.0	EC003015
ETIM 8.0	EC003015
ETIM 9.0	EC003015
ETIM 10.0	EC003015

The Sensor People

Leuze electronic GmbH + Co. KG
In der Braike 1, D-73277 Owen/Germany

info@leuze.com • www.leuze.com
Phone: +49 7021 573-0 • Fax: +49 7021 573-199

We reserve the right to make technical changes
eng • 2026-02-12

2/4

Dimensioned drawings

Leuze

All dimensions in millimeters

Electrical connection

Connection 1

Function	Activation output
	Signal IN
	Voltage supply
	Warning input
Type of connection	Terminal
No. of pins	6 -pin

Electrical connection

Leuze

Terminal	Assignment
1	VIN
2	GND
3	OUT 1
4	OUT 2
5	OUT WARN
6	OUT V

Accessories

Power supply units

	Part no.	Designation	Article	Description
	50110748	NT 24-24W	Power supply unit	Type of power supply unit: Plug-in power supply unit Output: 24 V DC, 1 A Input: 110 ... 240 V AC, 50 ... 60 Hz

Note
✎ A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.