## Leuze

## **Technical data sheet Optical data transmission**

Part no.: 50134399 DDLS 508i 120.3 H



The Sensor People In der Braike 1, D-73277 Owen/Germany

Leuze electronic GmbH + Co. KG

info@leuze.com • www.leuze.com changes Phone: +49 7021 573-0 • Fax: +49 7021 573-199 eng • 2025-04-05

### **Technical data**

#### Basic data

Encoding

Basic data	
Series	DDLS 500
Special version	
Special version	Heating
	Not influenced by reflective surfaces
	Operation of parallel light axes
	Remote diagnosis via web server
Optical data	
Working range	100 120,000 mm
Light source	Laser
Transmission frequency	F3
Opening angle	1 °
Electrical data	
Performance data	
Supply voltage U <sub>B</sub>	18 30 V, DC
Inputs	
Number of digital switching inputs	1 Piece(s)
Outpute	
Outputs Number of digital switching outputs	1 Piece(s)
number of argital switching outputs	111000(3)
Interface	
Transmission protocol	TCP/IP 100 Mbit
Туре	EtherNet TCP/IP
Ethernet Architecture	Transport
	Transparent None
Address assignment	100 Mbit/s
Transmission speed Function	Process
Switch functionality	None
•	
Transmission protocol	TCP/IP , UDP
Connection	
Number of connections	2 Piece(s)
	211000(3)
Connection 1	
Type of connection	Connector
Designation on device	POWER
Thread size	M12
Туре	Male
No. of pins	5 -pin
Encoding	A-coded
Connection 2	
Type of connection	Connector
Designation on device	BUS
Thread size	M12
Туре	Female
No. of pins	4 -pin
E	D stated

D-coded


# Leuze


#### Mechanical data


Mechanical data	
Dimension (W x H x L)	100 mm x 156 mm x 99.5 mm
Housing material	Metal
Net weight	1,255 g
Operation and display	
Type of display	Bar graph
	LED
Type of configuration	Software
	Via web browser
Environmental data	
Ambient temperature, operation	-35 50 °C
Ambient temperature, storage	-35 70 °C
Certifications	
Degree of protection	IP 65
Approvals	c UL US
Test procedure for EMC in accordance	EN 1000-6-4
with standard	EN 61000-6-2
Test procedure for noise in accordance with standard	EN 60068-2-64
Test procedure for oscillation in accordance with standard	EN 60068-2-6
Test procedure for shock in accordance with standard	EN 60068-2-27
Classification	
Customs tariff number	84718000
ECLASS 5.1.4	19039001
ECLASS 8.0	19179090
ECLASS 9.0	19179090
ECLASS 10.0	19170506
ECLASS 11.0	19170506
ECLASS 12.0	19170506
ECLASS 13.0	19170506
ECLASS 14.0	19170506
ECLASS 15.0	19170506
ETIM 5.0	EC000515
ETIM 6.0	EC000515
ETIM 7.0	EC000515
ETIM 8.0	EC000515
ETIM 9.0	EC000515
ETIM 10.0	EC000515

### **Dimensioned drawings**

All dimensions in millimeters







A Middleaxis Transmitter

B Center axis of transmitter and receiver

C Center axis of receiver


Leuze

#### **Electrical connection**

Connection 1	POWER
Function	Signal IN
	Signal OUT
	Voltage supply
Type of connection	Connector
Thread size	M12
Туре	Male
Material	Metal
No. of pins	5 -pin
Encoding	A-coded

#### Pin **Pin assignment**

1 2	VIN IO1	
3	GND	3 1
4	102	
5	FE/SHIELD	4



#### **Connection 2**


Connection 2	BUS	
Function	BUS IN	
Type of connection	Connector	
Thread size	M12	
Туре	Female	
Material	Metal	
No. of pins	4 -pin	
Encoding	D-coded	

Leuze electronic GmbH + Co. KG

Pin	Pin assignment	
1	TD+	
2	RD+	
3	TD-	
4	RD-	

### **Operation and display**

LED	)	Display	Meaning
1 AUT		Off	Operating mode not active
		Green, continuous light	Operating mode "Automatic"
2 1	MAN	Off	Operating mode not active
		Green, continuous light	Operating mode "Manual"
3 /	ADJ	Off	Operating mode not active
		Green, continuous light	Operating mode "Adjust"
1 1	LAS	Off	Operating mode not active
		Green, continuous light	Operating mode "Alignment-laser mounting support"
	LLC	Off	Operating mode not active
		Green, continuous light	LLC without interruption
		Red, continuous light	LLC interrupted at least once
	PWR	Off	No supply voltage
		Green, flashing	Device ok, initialization phase
		Green, continuous light	Data transmission active
		Red, flashing	Data transmission interrupted
		Red, continuous light	Device error
	ТМР	Off	Operating temperature OK
		Orange, continuous light	Operating temperature critical





## Leuze

### **Operation and display**

## Leuze

LE	D	Display	Meaning
7	ТМР	Red, continuous light	Operating temperature exceeded or not met
8	LSR	Off	With function reserve
		Orange, continuous light	Device OK, warning set
9	BUS	Off	not active for the DDLS 508i
10	OLK	Off	Fault
		Green, continuous light	No data transmission
		Orange, continuous light	Data transmission active
11	ERL	Off	Link OK
		Orange, continuous light	Missing link (Ethernet cable connection) on the second device
		Red, continuous light	No cable-connected link to the connected device
12	LINK	Off	No cable-connected link to the connected device
		Green, continuous light	Link OK
		Orange, continuous light	Data transmission active
13	SIGNAL QUALITY	2 red, 2 orange and 4 green	Received signal level

#### Suitable receivers

 Part no.	Designation	Article	Description
50134400	DDLS 508i 120.4 H	Optical data transmission	Special version: Heating, Not influenced by reflective surfaces, Operation of parallel light axes, Remote diagnosis via web server Working range: 100 120.000 mm Transmission frequency: F4 Interface: EtherNet TCP/IP Connection: Connector, M12

#### Part number code

Part designation: DDLS 5XXX YYY.Z A B CC

DDLS	Optical transceiver for digital data transmission
5XXX	Series 508i: without integrated web server for remote diagnostics 508i: with integrated web server for remote diagnostics 538: without integrated web server for remote diagnostics (EtherCAT) 548i: with integrated web server for remote diagnostics
YYY	Range for data transmission in m
Z	Frequency of the transmitter 0: Frequency F0 1: Frequency F1 2: Frequency F2 3: Frequency F3 4: Frequency F4
A	Option L: integrated laser alignment aid (for transmitter/receiver) n/a: standard
В	Special equipment H: with heating n/a: no special equipment
cc	Special equipment W: transmission optics with larger opening angle (on request) n/a: no special equipment

	Note
6	S A list with all available device types can be found on the Leuze website at www.leuze.com.

#### Notes

## Leuze

#### Observe intended use!

✤ This product is not a safety sensor and is not intended as personnel protection.

b The product may only be put into operation by competent persons.

	For UL applications:
	♣ For UL applications, use is only permitted in Class 2 circuits in accordance with the NEC (National Electric Code).
	ATTENTION! INVISIBLE LASER RADIATION - CLASS 1M LASER PRODUCT
	Do not expose users of telescopic optics! The device satisfies the requirements of IEC 60825-1:2007 (EN 60825-1:2007) safety regulations for a product of laser class 1M as well as the U.S. 21 CFR 1040.10 regulations with deviations corresponding to Laser Notice No. 50 from June 24, 2007.

#### ✤ Do not expose users of telescopic optics!

The device satisfies the requirements of IEC 60825-1:2007 (EN 60825-1:2007) safety regulations for a product of **laser class 1M** as well as the U.S. 21 CFR 1040.10 regulations with deviations corresponding to Laser Notice No. 50 from June 24, 2007.

- beam or in the direction of reflecting beams.
- CAUTION! The use of operating and adjusting devices other than those specified here or the carrying out of differing procedures may lead to dangerous exposure to radiation!

The use of optical instruments or devices (e.g., magnifying glasses, binoculars) in combination with the device increases the danger of eye damage.

 $\ensuremath{\mathfrak{b}}$  Observe the applicable statutory and local laser protection regulations.

<sup>th</sup> The device must not be tampered with and must not be changed in any way. There are no user-serviceable parts inside the device. Repairs must only be performed by Leuze electronic GmbH + Co. KG.

#### Accessories

#### Connection technology - Connection cables

	Part no.	Designation	Article	Description
	50132079	KD U-M12-5A-V1- 050	Connection cable	Connection 1: Connector, M12, Axial, Female, A-coded, 5 -pin Connector, LED: No Connection 2: Open end Shielded: No Cable length: 5.000 mm Sheathing material: PVC
Ŵ	50135074	KS ET-M12-4A-P7- 050	Connection cable	Suitable for interface: Ethernet Connection 1: Connector, M12, Axial, Male, D-coded, 4 -pin Connector, LED: No Connection 2: Open end Shielded: Yes Cable length: 5.000 mm Sheathing material: PUR

#### Accessories

## Leuze

### Connection technology - Interconnection cables

	Part no.	Designation	Article	Description
	50137078	KSS ET-M12-4A- M12-4A-P7-050	Interconnection cable	Suitable for interface: Ethernet Connection 1: Connector, M12, Axial, Male, D-coded, 4 -pin Connection 2: Connector, M12, Axial, Male, D-coded, 4 -pin Shielded: Yes Cable length: 5,000 mm Sheathing material: PUR
	50135081	KSS ET-M12-4A- RJ45-A-P7-050	Interconnection cable	Suitable for interface: Ethernet Connection 1: Connector, M12, Axial, Male, D-coded, 4 -pin Connection 2: RJ45 Shielded: Yes Cable length: 5,000 mm Sheathing material: PUR

### Connection technology - Connectors

	Part no.	Designation	Article	Description
	50020501	KD 095-5A	Connector	Connection: Connector, M12, Axial, Female, A-coded, 5 -pin
Committee of	50112155	S-M12A-ET	Connector	Suitable for interface: Ethernet Connection: Connector, M12, Axial, Male, D-coded, 4 -pin

#### Services

	Part no.	Designation	Article	Description
, U	S981001	CS10-S-110	Start-up support	Details: Performed at location of customer's choosing, duration: max. 10 hours. Conditions: Devices and connection cables are already mounted, price not including travel costs and, if applicable, accommodation expenses.
	S981005	CS10-T-110	Product training	Details: Location and content to be agreed upon, duration: max. 10 hours. Conditions: Price not including travel costs and, if applicable, accommodation expenses.

	Note
1	S A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.