

KF-L-10MLD-20

Cod. art. 50117743

Fibra ottica, unidirezionale

Dati tecnici

Tipo di fibra ottica
Particolarità

Nucleo a fibre multiple
Riconoscimento della
superficie (larghezza del
campo luminoso = 5,44 mm)
-55°C ... +70°C
R25
Ø2,2 mm
16x Ø0,265 mm
Ø1,0 mm
2010 mm
2 pezzi

Temperatura operativa
Raggio di curvatura min.
Diametro esterno fibra ottica
Diametro attivo fibra
Pezzo più piccolo riconoscibile
Lunghezza totale
Unità d'imballo

Caratteristiche Features



- 1) Impostazione di amplificatore per fibra ottica: max. tempo di reazione, max. amplificazione, min. soglia di commutazione / Adjustment on fiber optics amplifier: max. response time, max. gain, min. switching threshold

KF-L-10MLD-20

Part No. 50117743

Fiber, throughbeam

Specifications

Fiber type
Specific feature

Multiple core
Array (width = 5.44 mm)

Operating temperature
Min. bending radius
Fiber jacket diameter
Active fiber diameter
Smallest detectable object
Total length
Packaging unit

-55°C ... +70°C
R25
Ø2.2 mm
16x Ø0.265 mm
Ø1.0 mm
2010 mm
2 pieces

Portata limite tipica ¹⁾ Typ. scanning range limit ¹⁾

LV463I.XR	2250 mm
LV463.XR	1125 mm
LV463B, LV463.XV	770 mm
LV463	450 mm
LV462	260 mm
LV461	150 mm

Disegno quotato/Dimensioned drawing

