

KF-LW-FU57-20

Cod. art. 50117745

Fibra ottica, unidirezionale

KF-LW-FU57-20

Part No. 50117745

Fiber, throughbeam

Dati tecnici

Tipo di fibra ottica	Alta flessibilità
Particolarità	Uscita laterale del fascio
Temperatura operativa	-40°C ... +70°C
Raggio di curvatura min.	R1
Diametro esterno fibra ottica	Ø1,0mm
Diametro attivo fibra	Ø0,5mm
Pezzo più piccolo riconoscibile	Ø0,1mm
Lunghezza totale	2010mm
Unità d'imballo	2 pezzi

Caratteristiche

Features



- 1) Impostazione di amplificatore per fibra ottica: max. tempo di reazione, max. amplificazione, min. soglia di commutazione / Adjustment on fiber optics amplifier: max. response time, max. gain, min. switching threshold

Specifications

Fiber type	High flexible
Specific feature	Sideview
Operating temperature	-40°C ... +70°C
Min. bending radius	R1
Fiber jacket diameter	Ø1.0mm
Active fiber diameter	Ø0.5mm
Smallest detectable object	Ø0.1mm
Total length	2010mm
Packaging unit	2 pieces

Portata limite tipica ¹⁾ Typ. scanning range limit ¹⁾

LV463I.XR	750mm
LV463.XR	375mm
LV463B, LV463.XV	260mm
LV463	150mm
LV462	85mm
LV461	50mm

Disegno quotato/Dimensioned drawing

