

## Technical data sheet

## Tower light element

Part no.: 50130435

E7-V1-BZ1

### Contents

- Technical data
- Notes
- Accessories



For illustration purposes only



## Technical data

### Basic data

Series	E7
Suitable for	Tower light elements of the E7 series
Type of signaling	Acoustic

### Electrical data

#### Performance data

Supply voltage $U_B$	24 V, DC, 10 %
Current consumption, max.	92 mA

### Mechanical data

Design	Cylindrical
Dimension ( $\varnothing$ x L)	70 mm x 70 mm
Housing material	Plastic
Net weight	102 g
Type of fastening	Bayonet system

### Operation and display

Operational controls	DIP switch
Function of the operational control	Selection of tone type

### Environmental data

Ambient temperature, operation	-30 ... 60 °C
--------------------------------	---------------

### Certifications

Degree of protection	IP66, UL Type 4/4X/13
Approvals	c UL US

### Acoustic data

Tone type	Continuous or pulse tone
Sound pressure	100 ... 100 dB
Number of tones	1 Piece(s)

### Classification

Customs tariff number	85318070
ECLASS 5.1.4	27371237
ECLASS 8.0	27371237
ECLASS 9.0	27371237
ECLASS 10.0	27371237
ECLASS 11.0	27371237
ECLASS 12.0	27371237
ECLASS 13.0	27371237
ECLASS 14.0	27371237
ECLASS 15.0	27371237
ECLASS 16.0	27371237
ETIM 5.0	EC001261
ETIM 6.0	EC001261
ETIM 7.0	EC001261
ETIM 8.0	EC001261
ETIM 9.0	EC001261
ETIM 10.0	EC001261

## Notes



### Observe intended use!



- ⌘ This product is not a safety sensor and is not intended as personnel protection.
- ⌘ The product may only be put into operation by competent persons.
- ⌘ Only use the product in accordance with its intended use.



### For UL applications:



- ⌘ For UL applications, use is only permitted in Class 2 circuits in accordance with the NEC (National Electric Code).

## Accessories

### Mounting

	Part no.	Designation	Article	Description
	50130436	E7-MH1	Tower light element	Connection: Terminal, Tension spring technology Design: Cylindrical Version: Horizontal mounting Fastening, at system: Screw type / horizontal Lens modules: Max. 5 pieces Module holder: One side Ambient temperature: -30 ... 60 °C Degree of protection: IP 66
	50130440	E7-MP1-100	Tower light element	Connection: Terminal, Tension spring technology Design: Cylindrical Version: Base mounting Fastening, at system: Screw type / horizontal Lens modules: Max. 5 pieces Module holder: One side Ambient temperature: -30 ... 60 °C Degree of protection: IP 66
	50130437	E7-MW1	Tower light element	Connection: Terminal, Tension spring technology Design: Cylindrical Version: Bracket mounting Fastening, at system: Screw type / vertical Lens modules: Max. 5 pieces Module holder: One side Ambient temperature: -30 ... 60 °C Degree of protection: IP 66
	50130438	E7-MW2	Tower light element	Connection: Terminal, Tension spring technology Design: Cylindrical Version: Bracket mounting Fastening, at system: Screw type / vertical Lens modules: Max. 10 pieces Module holder: Two-sided Ambient temperature: -30 ... 60 °C Degree of protection: IP 66

#### Note



A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.